

SAFETY DATA SHEET

Page : 1

Revised edition no : 6

Date : 9/7/2008

Supersedes : 7/2/2003

VASELINE SPRAY

PARA

www.lisam.com



N : Dangerous for the environment



F+ : Extremely flammable



Xi : Irritant

Producer

DL CHEMICALS

Roterijstraat 201-203

B-8793 Waregem Belgique-Belgie

Tel. +32 56 62 70 51

In case of emergency : + 32 70 245 245

Responsible for distribution

DL CHEMICALS

Roterijstraat 201-203

B-8793 Waregem Belgique-Belgie

Tel. +32 56 62 70 51

In case of emergency : + 32 70 245 245

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Identification of the product : Aerosols dispensers.
Company identification : See distributor.
Use : Industrial.

2. HAZARDS IDENTIFICATION

Risk Phrases : Extremely flammable. Irritating to eyes.
Environmental hazard : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Primary route of exposure : Eyes contact.
Symptoms relating to use
- Inhalation : Cough.
- Skin contact : Not expected to present a significant skin hazard under anticipated conditions of normal use.
- Eye contact : Redness. Tears. Pain. Blurred vision.
- Ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Dangerous product (Directive 1999/45/EC). Substances presenting a health or environmental hazard within the meaning of Directive 67/548/EEC

Substance name	Contents	CAS No / EC No / Index No	Symbol(s)	R-Phrase(s)
<u>Naphtha (petroleum), hydrotreated heavy (benzeen < 0.1%)</u>	: 10 to 25 %	64742-48-9 / 265-150-3 / ----	Xn	65-66
<u>Propan-2-ol</u>	: 10 to 25 %	67-63-0 / 200-661-7 / 603-117-00-0	F Xi	11-36-67
<u>Pentane</u>	: 25 to 50 %	109-66-0 / 203-692-4 / 601-006-00-1	F+ Xn N	12-51/53-65-66-67
<u>Propane</u>	: 2.5 to 10 %	74-98-6 / 200-827-9 / 601-003-00-5	F+	12
<u>Isobutane</u>	: 2.5 to 10 %	75-28-5 / 200-857-2 / 601-004-00-0	F+	12

4. FIRST AID MEASURES

First aid measures
- Inhalation : Assure fresh air breathing.
- Skin contact : Wash skin thoroughly with mild soap and water.
- Eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking, tears or redness persist.
- Ingestion : Rinse mouth.

DL CHEMICALS

Roterijstraat 201-203 B-8793 Waregem Belgique-Belgie

Tel. +32 56 62 70 51

In case of emergency : + 32 70 245 245

SAFETY DATA SHEET

Page : 2

Revised edition no : 6

Date : 9/7/2008

Supersedes : 7/2/2003

VASELINE SPRAY

PARA

www.lisam.com

5. FIRE-FIGHTING MEASURES

Flammable class	: Extremely flammable.
Prevention	: No naked lights. No smoking.
Extinguishing media	: Dry chemical. Carbon dioxide. Foam. Water.
Surrounding fires	: Apply water spray or fog to cool nearby equipment.
Specific hazards	: Vapour mixes readily with air, forming explosive mixtures.
Protection against fire	: Do not enter fire area without proper protective equipment, including respiratory protection.
Special procedures	: Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	: Equip cleanup crew with proper protection.
Environmental precautions	: Notify authorities if product enters sewers or public waters. Prevent entry to sewers and public waters.
Clean up methods	: Remove ignition sources. Clean up any spills as soon as possible, using an absorbent material to collect it. Waste mixtures containing propane/butane may not enter into drains or sewers where vapours could accumulate and ignite.

7. HANDLING AND STORAGE

General	: Do not breathe gas, fumes, vapour or spray.
Precautions in handling and storage	: Keep away from sources of ignition - No Smoking.
Storage	: Store in dry, cool, well-ventilated area. Keep container closed when not in use.
Storage - away from	: Direct sunlight. Heat sources. Sparks. Open flame.
Handling	: Ensure prompt removal from eyes. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection	
- Respiratory protection	: No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation.
- Skin protection	: Gloves.
- Eye protection	: Goggles.
Industrial hygiene	: Provide good ventilation in process area to prevent formation of vapour.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20 °C	: Liquid.
Odour	: Characteristic.
Solubility in water	: Soluble
Other data	: See Heading : Information on ingredients.

10. STABILITY AND REACTIVITY

Hazardous decomposition products	: None under normal conditions.
Hazardous reactions	: None under normal conditions.
Hazardous properties	: In use, may form flammable/explosive vapour-air mixture.
Conditions to avoid	: Heat. Direct sunlight. Open flame. Sparks.

SAFETY DATA SHEET

Page : 3

Revised edition no : 6

Date : 9/7/2008

Supersedes : 7/2/2003

VASELINE SPRAY

PARA

www.lisam.com

11. TOXICOLOGICAL INFORMATION

Rat oral LD50 [mg/kg] : No data available.
On ingredients : See Heading : Information on ingredients.

12. ECOLOGICAL INFORMATION

Ecological effects information : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
LC50-96 Hour - fish [mg/l] : No data available.
On ingredients : See Heading : Information on ingredients.

13. DISPOSAL CONSIDERATIONS

General : Avoid release to the environment.
Container under pressure. Do not drill or burn even after use.
WHEN TOTALLY EMPTY, containers are recyclable like any other packing.
When not empty dispose of this container at hazardous or special waste collection point.
Dispose in a safe manner in accordance with local/national regulations.

14. TRANSPORT INFORMATION

Labelling ADR : Extremely flammable.
- Tremcard nr. : 20G26-2
ADR/RID : Class 2

15. REGULATORY INFORMATION

Symbol(s) : Xi : Irritant
F+ : Extremely flammable
N : Dangerous for the environment
R Phrase(s) : R12 : Extremely flammable.
R36 : Irritating to eyes.
R51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66 : Repeated exposure may cause skin dryness or cracking.
R67 : Vapours may cause drowsiness and dizziness.
S Phrase(s) : S2 : Keep out of the reach of children.
S9 : Keep container in a well-ventilated place.
S16 : Keep away from sources of ignition - No smoking.
S26 : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S45 : In case of accident or if you feel unwell, seek medical advice immediately (show the label when possible).
S37 : Wear suitable gloves.
S57 : Use appropriate container to avoid environmental contamination.
S59 : Refer to manufacturer/supplier for information on recovery/recycling.

16. OTHER INFORMATION

Further information : None.

The contents and format of this SDS are in accordance with EEC Commission Directive 2001/58EC.

SAFETY DATA SHEET	Page : 4
	Revised edition no : 6
VASELINE SPRAY	Date : 9/7/2008
	Supersedes : 7/2/2003
	PARA www.lisam.com

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document